

# OSC D - Direct-Coupled Frequency Inverter Screw Compressor Series



## OSC D (18,5-315 kW)

MODEL	Working Pressure	Capacity (FAD) m <sup>3</sup> /min.	Motor Power		dB(A)	Weight (kg)	Connection Diameter	Dimensions (mm)		
	Bar		kW	HP				Width	Length	Height
OSC 18 D	7.5	3.27	18.5	25	71	470	3/4 "	900	1600	1410
	10	2.85								
	13	2.43								
OSC 22 D	7.5	3.82	22	30	71	500	3/4 "	900	1600	1410
	10	3.36								
	13	2.89								
OSC 30 D	7.5	5.04	30	40	71	700	1 "	900	1600	1410
	10	4.47								
	13	3.89								
OSC 37 D	7.5	6.42	37	50	71	840	1 1/4 "	1150	1500	1610
	10	5.58								
	13	4.77								
OSC 45 D	7.5	7.62	45	60	72	920	1 1/2 "	1150	1500	1610
	10	6.7								
	13	5.79								
OSC 55 D	7.5	10.18	55	75	74	1450	1 1/2 "	1450	1600	1750
	10	8.86								
	13	7.53								
OSC 75 D	7.5	13.29	75	100	75	2120	2 "	1650	2000	1900
	10	11.74								
	13	10.17								
OSC 90 D	7.5	16.94	90	125	75	2350	2 "	1650	2000	1900
	10	14.69								
	13	12.51								
OSC 110 D	7.5	20.29	110	150	76	2740	2 "	1600	3200	1855
	10	17.76								
	13	15.28								
OSC 132 D	7.5	23.86	132	180	77	3250	3 "	1600	3200	1855
	10	21.07								
	13	18.28								
OSC 160 D	7.5	30.23	160	220	77	3980	3 "	1950	3500	2055
	10	26.11								
	13	21.62								
OSC 200 D	7.5	41.02	200	270	78	5310	4 "	2150	3700	2350
	10	34.22								
	13	28.37								
OSC 250 D	7.5	50.21	250	340	78	6250	4 "	2150	3700	2350
	10	42.1								
	13	35.69								
OSC 315 D	7.5	55.25	315	430	79	6550	4 "	2150	3900	2350
	10	46.42								
	13	39.75								

- Compressor performance is measured according to ISO 1217: 2009 Annex C with reference to 1 bar inlet pressure and 20 °C ambient temperature.

- U: Direct-Coupled, D: Direct-Coupled with VFD control.