


INNOVATION PM COMPRESSOR

- ✓ IP65 protection grade
- ✓ PM motor free bearing maintenance
- ✓ IE4 high efficiency and oil cooling PM motor
- ✓ Latest VSD technology
- ✓ Direct connection, max 3000RPM
- ✓ Integrated air tank
- ✓ PLC control, easy maintenance
- ✓ Latest china-Japan technology cooperation

PM2





Ultra-quiet

Oil cooling PM motor help reduce noise level,desgin for site operation.

Constant pressure

Latest VSD technology to achieve constant pressure state,reflect the true sense of energy-saving.

Hgih Reliability

The PM2 compressor has been proofed in more than 50 counries,from cold area to tropical area,its high reiability is always been so.

Technical Specification

| Model | KW | HP | Capacity(m ³ /min) | Pressure (BAR) | Dimension (mm) | Weight (KG) | Size |
|---------------|-----|----|-------------------------------|----------------|----------------|-------------|--------|
| SCR10PM2 - 7 | 7.5 | 10 | 0.46 - 1.15 | 7 | 1197x500x1125 | 280 | RC 1/2 |
| SCR10PM2 - 8 | | | 0.41 - 1.1 | 8 | | | |
| SCR10PM2 - 10 | | | 0.48 - 0.95 | 10 | | | |
| SCR15PM2 - 7 | 11 | 15 | 0.72 - 1.75 | 7 | 1197x605x1220 | 320 | RC 3/4 |
| SCR15PM2 - 8 | | | 0.69 - 1.7 | 8 | | | |
| SCR15PM2 - 10 | | | 0.75 - 1.5 | 10 | | | |
| SCR20PM2 - 7 | 15 | 20 | 0.96 - 2.4 | 7 | 1197x605x1220 | 340 | RC 3/4 |
| SCR20PM2 - 8 | | | 0.92 - 2.3 | 8 | | | |
| SCR20PM2 - 10 | | | 1.0 - 2.0 | 10 | | | |

Note: > The capacity is measured as GB3853 standard.(equivalent to ISO1217 Annex C)

> Standard voltage is 380V/50HZ/3P,other voltage is available.

> Alpine/high altitude,high temperature,high humidity,high dust loads or other adverse working conditions will require specialized custom designs.These are available on special request.

> We reserve the right to make improvement of the compressor without prior notice.